

LOCTITE® PRE-APPLIED PRODUCT SELECTOR GUIDE

Product Number	Item Number	IDH Number	Package Size	Product Name	Product Description
Loctite® Vibra-Seal® products, all are 300°F rated, reusable, and resistant to most fluids.					
503™	25662	135370	1 Liter	Loctite® 503™ Vibra-Seal® – White	This is a low viscosity sealant that will provide “constant on” torque. Also meets NSF® approval.
	28264	233081	10 Liter	Loctite® 503™ Vibra-Seal® – White	
	25663	231491	152 Liter	Loctite® 503™ Vibra-Seal® – White	
503 HV™	28262	233059	1 Liter	Loctite® 503 HV™ Vibra-Seal® – White	This is a high viscosity sealant that will provide gap filling capability. Also meets NSF® approval.
	25664*	231493	10 Liter	Loctite® 503 HV™ Vibra-Seal® – White	
	25665	231495	152 Liter	Loctite® 503 HV™ Vibra-Seal® – White	
516™	25666	142724	1 Liter	Loctite® 516™ Vibra-Seal® – Dark Orange	This is a high viscosity sealant, with “constant on” torque.
	25667*	231496	10 Liter	Loctite® 516™ Vibra-Seal® – Dark Orange	
	25668	231498	152 Liter	Loctite® 516™ Vibra-Seal® – Dark Orange	
517™	25669*	231500	10 Liter	Loctite® 517™ Vibra-Seal® – Dark Orange	This is a low viscosity sealant, with “constant on” torque.
	25670	231502	152 Liter	Loctite® 517™ Vibra-Seal® – Dark Orange	
Loctite® Dri-Seal™ products, all are 300°F rated, reusable, and resistant to most fluids.					
513™	51343	234311	1 Liter	Loctite® 513™ Dri-Seal™ – White	High temperature (350°F) sealant for metal and plastics. NSF® approved. Flow coatable.
	51391	234327	18 Liter	Loctite® 513™ Dri-Seal™ – White	
	51397*	234329	180 Liter	Loctite® 513™ Dri-Seal™ – White	
513 HV™	33956	269737	18 Liter	Loctite® 513 HV™ Dri-Seal™ – White	High viscosity, high temperature (350°F) sealant for metal and plastics. NSF® approved. Flow coatable.
	26959	270589	180 Liter	Loctite® 513 HV™ Dri-Seal™ – White	
5030™	34578	318823	10 Liter	Loctite® 5030™ Dri-Seal™ – Blue	UL® approved sealant for propane, similar properties as product number 503.
	34579	–	152 Liter	Loctite® 5030™ Dri-Seal™ – Blue	
Loctite® Dri-Loc® rated at 300°F unless specified. These products harden after installation.					
200™	12402	228382	40 lbs. Pail	Loctite® 200™ Dri-Loc® – Yellow	High strength threadlocker and sealant. Suitable for phosphate and oil substrates only.
201™	12506	985235	20 lbs. Kit	Loctite® 201™ Dri-Loc® – Dark Yellow	400°F, high strength threadlocker and sealant. Meets GM 6194, able to be used on plated parts and organic coatings. Use with P3™ caps. Meets GMW14657C.
	38347	985234	40 lbs. Pail	Loctite® 201™ Dri-Loc® – Dark Yellow	
202™	12403	228380	40 lbs. Pail	Loctite® 202™ Dri-Loc® – Green	Medium strength threadlocker and sealant.
203™	12405	228381	40 lbs. Pail	Loctite® 203™ Dri-Loc® – Silver	Low strength threadlocker and sealant.
204™	18723	229815	40 lbs. Pail	Loctite® 204™ Dri-Loc® – Red	Designed for plated and stainless steel fasteners. High dried adhesion, high strength.
2045™	36806	444376	20 lbs. Kit	Loctite® 2045™ Dri-Loc® – Red	Designed for plated and stainless steel fasteners. High dried adhesion, high strength, fast cure, high temperature (400°F), meets GME151 & WX200. Use with Loctite® P2™ and P3™ caps.
STS™	18872	229855	40 lbs. Pail	Loctite® STS™ Dri-Loc® – Light Blue	Sealing and medium strength threadlocking, fast cure. Meets GM6124m, GM14657A, Chrysler MSc 76-b.
205™	19840	230087	40 lbs. Pail	Loctite® 205™ Dri-Loc® – Bright Orange	High strength, low/controlled on torque assembly. Meets GM6175M.
2060 UV™	–	1062864	3 kg kit	Loctite® 2060 UV™ Dri-Loc®	Medium to high strength threadlocker, very dry to touch, bowl and auto feeding capable. Works well on all finishes. Please note that the Loctite® 2060™ Dri-Loc® uses its own special microcaps #1062863.
	–	1062863	3 kg kit	Microcaps for Loctite® 2060 UV™ Dri-Loc®	
Loctite® Brass-Loc® products threadlocker and sealant.					
2020™	30177	234646	40 lbs. Pail	Loctite® 2020™ Brass-Loc®	Low to medium strength, will not corrode brass. Also works on plated finishes and stainless.
Loctite® Dri-Loc® Activator - To be used and mixed with all Loctite® Dri-Loc® products as the reactive agent (These products are NOT for use with Loctite® 2060™ Dri-Loc®).					
P2™	12057	228328	2 lbs.	Loctite® P2™ Dri-Loc® Activator	Small microcapsules, excellent for all size fasteners, especially fine threads.
	19881	230105	5 lbs.	Loctite® P2™ Dri-Loc® Activator	Small microcapsules, excellent for all size fasteners, especially fine threads.
P3™	36933	451935	1 kg	Large Microcapsules for M6 and larger	Works best with Loctite® 2045™, 201™, 204™ and STS™ Dri-Loc® products. NOT suggested for fine threads and small fasteners M6 or smaller.
Loctite® Pre-Applied Anti-Seize, a non-curing product.					
N/A	17015	229430	40 lbs. Pail	Anti-Seize	To prevent galling and corrosion of metals, especially stainless steel and aluminum.

* Special Package - 30 day lead time required.