



Loctite® 55™



LOCTITE®



A new solution from the company you know and trust.

Loctite® 55™
Just *one* gets it done™



Here's what other plumbers are saying about Loctite® 55™ Pipe Sealing Cord:

"When you use a new product, you're normally leery. There's nothing worse than doing a whole series of fittings and finding out the first one leaks. But Loctite® 55™ worked perfectly. There were no leaks at all. I would strongly recommend it to anyone."

– Jeff Suite

"I used to use pipe dope. But Loctite® 55™ is faster, cleaner, and trouble-free. It's amazing material."

– Jerome Rondeau

Certifications:



Underwriters Laboratories (UL)
UL listed for use on threaded joints.



NSF International
Certified to ANSI/NSF Standard 61 for potable water.



CSA International
Certified to CSA International requirements for Natural and L.P. gases.

J U S T O N E G E T S I T D O N E .™

U.S.A.

Henkel Corporation
Engineering Adhesives
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067
Tel: 860.571.5100
Fax: 860.571.5465
www.henkel.us
www.loctite.com

Canada

Henkel Canada Corporation
Engineering Adhesives
2225 Meadowpine Blvd.
Mississauga, Ontario L5N 7P2
Tel: 1.800.263.5043
Tel: 905.814.6511
Fax: 905.814.5391

Loctite, 55, and "Just one gets it done" are trademarks of Henkel Corporation, U.S.A. UL is a registered trademark of Underwriters Laboratories. NSF is a registered trademark of NSF International. CSA is a registered trademark of CSA International.
© Henkel Corporation, 2006. All rights reserved. 3796/LT-3631 (7/06)





Item #	Container Size
35082	5,700" (145m)
39036	1,968" (50m)

Loctite® 55™

Just **ONE** replaces tape, dope, and wicking all in one convenient package.

Just **ONE** lasts as long as up to nine rolls of thread tape.

Just **ONE** outperforms the rest in high-pressure applications.

Just **ONE** is adjustable so there's no need to reapply.

Loctite® 55™
Just **ONE** gets it done.™

Loctite® 55™ Pipe Sealing Cord is a general purpose threaded pipe and fitting sealant. It is a non-curing, coated multifilament cord that seals out air and other common gases and fluids. It comes in a handy container with a built-in cutter to easily apply the proper amount of cord.

Loctite® 55™ is recommended for sealing metal and plastic tapered pipe threads and fittings up to 4" NPT. It has a temperature resistance up to 150°C (300°F). Loctite® 55™ allows assemblies to be adjusted after assembly, making it particularly well suited for those applications where small adjustments are necessary before use.

FEATURES:

- Over 350 applications per container*
- Integrated cutting tool for easier application
- 5,700 inches of sealing cord per container
- Easy-to-use packaging
- Requires similar application techniques as thread tape (nothing new to learn)
- Won't unspool
- Tough, durable container
- Seals out air, common fluids, petroleum-based fluids, propane and natural gas

* On 1/2" metal pipe using 6 wraps per application.

BENEFITS:

- Allows for post assembly adjustments up to 90°
- Resistant to common solvents and chemicals
- Seals high pressure lines up to 10,000 psi
- Outseals tapes and dopes
- No curing, no waiting
- Easy and effective
- Faster and cleaner to use than dopes
- Provides lubrication for assembly/disassembly

USE LOCTITE® 55™ ON:

- Black Iron
- Steel
- Plastic
- Stainless Steel
- Brass

TYPICAL APPLICATIONS INCLUDE:

- Tanks
- In-Plant Utilities
- Natural & L.P. Gas Lines
- Steam Systems
- Oil Lines
- Pumps
- Drums
- Pneumatics
- Water Lines

Choose Loctite® 55™ for your next job and finish faster. For the distributor nearest you, visit www.loctite.com.

Loctite® 55™
It's as easy as 1, 2, 3...



1

Hold the end of the cord on the first few threads.



2

Wind inside and diagonally across the threads.



3

Sever cord with the dispenser's built-in cutting blade.

J U S T O N E G E T S I T D O N E .™